

CLAIMS

1. A signal processing system for processing an input signal, comprising:
a plurality of resonators, each resonator having parameters characterizing it, for
processing the input signal to generate N individual output signals; and
5 a reconstructor
for weighting each of the N individual output signals using a corresponding weight
to generate N individual weighted signals; and
for superposing the N individual weighted signals to obtain M output signals;
whereby $N \in \mathbb{N}$ and $M \in \mathbb{N}$, and whereby one of the parameters or the weight is time
10 dependent.
2. The signal processing system of claim 1, wherein one of the N resonators is a
Lorentzian resonator.
3. The signal processing system of claim 1, wherein one or more of the plurality of
resonators are Lorentzian resonators, and wherein the N individual output signals are
15 fed to a mixing matrix for coupling of these N individual output signals.
4. The signal processing system of claim 1, wherein the plurality of resonators form a
dynamic filter array.
5. The signal processing system of claim 1, wherein the weight is time dependent and
frequency dependent.
- 20 6. The signal processing system of claim 1, wherein the reconstructor comprises circuitry
for dynamically calculating the corresponding weights used for weighting each of the
 N individual output signals.

09616020-071300

- 09616020-071300
7. The signal processing system of claim 1, wherein the reconstructor superposes the N individual weighted signals by a mathematical operation selected from a set of operations consisting of addition, subtraction, multiplication, division.
 8. The signal processing system of claim 1, wherein the reconstructor comprises an adder
5 for superposing the N individual weighted signals.
 9. The signal processing system of claim 1 further comprising an interface circuitry serving as interface to a back end system.
 10. The signal processing system of claim 1, wherein the back end system is a hearing aid, or a speech recognition system, or a speaker recognition system, or a pervasive
10 computing device, or a computer system.
 11. The signal processing system of claim 9, wherein the interface circuitry comprises an amplifier and loudspeaker.
 12. The signal processing system of claim 1, wherein one of the plurality of resonators comprises a coil, a resistor, and a capacitor.
 13. The signal processing system of claim 1, wherein one of the plurality of resonators
15 comprises a micromechanical element, preferably a cantilever.
 14. The signal processing system of claim 1, wherein one of the plurality of resonators is realized by a combination of a processor and a code that embodies an algorithm for execution by the processor.
 15. The signal processing system of claim 1, wherein the plurality of resonators and the
20 reconstructor are realized in a computer system comprising a processor and a code that when executed by the processor generates the M output signals.
 16. The signal processing system of claim 1, 9, 10, or 15, wherein the input signal is a voice signal.

17. The signal processing system of claim 1 or 15, wherein the M output signals represent a set of descriptors which describe properties of the input signal.
18. The signal processing system of claim 17, wherein the set of descriptors is usable by a speech recognition system or speaker recognition system.
- 5 19. The signal processing system of claim 1 or 15, wherein the N individual weighted signals identify different vowels and/or classes of consonants.
20. The signal processing system of claim 15, wherein the code embodies an algorithms for generating a descriptor sets for use in a speech recognition system or speaker recognition system.
- 10 21. The signal processing system of claim 14 or 20, wherein the algorithm represents a differential equation, preferably a second order equation.
22. The signal processing system of claim 1, wherein there is more than one input signal.
23. The signal processing system of claim 1 receiving L time signals which either make the parameters or the weights time dependent and wherein $L \in \mathbb{N}$.
- 15 24. The signal processing system of claim 23, wherein the L time signals are provided by a resonator, a reconstructor, or a computer.
25. Method for processing an input signal, comprising the steps:
- processing the input signal by means of a plurality of resonators, each resonator having parameters characterizing it, to generate N individual output signals;
- 20 weighting each of the N individual output signals using a corresponding weight to generate N individual weighted signals; and
- superposing the N individual weighted signals to obtain M output signals;

09616020-071300

26. A computer program element comprising:

5

superposing the N individual weighted signals to obtain M output signals;

10

15

superpose the N individual weighted signals to obtain M output signals;

20